

Apollo 48000

Air to air Floor Standing Heat Pump

ANDERSEN
Electric

Item no.: 1221



- Heating and cooling function
- Auto-function
- Dehumidification
- Energy saving solution (A+ / A++)
- Filter removes dust particles from the air
- Designed for Nordic climate (-25°C)
- Remote control with LCD display
- Suitable for large workshops, warehouses, offices etc.



Technical data

Max. heating capacity	18.5 kW
Power supply	220-240 VAC / 380-415 VAC
Nominal heating capacity	11.0 kW
SCOP/SEER	4.0 / 6.1
Energy class (heating/cooling)	A+ / A++
Tol	-25°C
Nominal cooling capacity	14.6 kW
Temperature range	17°C - 30°C
Refrigerant type	R32
Refrigerant charge (up to 5 meter pipe)	2.8 kg
Refrigerant piping (liquid side)	9.25 mm (3/8")
Refrigerant piping (gas side)	15.9 mm (5/8")
Max. refrigerant pipe length	40 m
Applicable area (approx.)	~370 m ²
Max. difference in level	20 m
Recommended cable (power cable)	5x1.5 mm ²
Recommended cable (signal cable)	3x1.5 mm ²

Indoor unit

Sound power level	66 dB (A)
Sound pressure level H/M/L	55/53/51.5 dB (A)
Air flow H/M/L	2413/2222/2027 m ³ /h
Dimension (WxHxD)	445x1934x600 mm
Weight	62 kg

Outdoor unit

Sound power level	70 dB (A)
Sound pressure level	65 dB (A)
Dimension (WxHxD)	1035x1333x415 mm
Weight	108 kg